## NSN 5305-01-129-4432



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-129-4432 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.607 inches and 0.686 inches **Fastener Length:** Between 0.671 inches and 0.718 inches **Head Style:** Hexagon **Head Height:** Between 0.105 inches and 0.120 inches Width Between Flats: Between 0.305 inches and 0.314 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Product Name:** Navy special project **Screw Material:** Steel comp e4340 or steel comp 8740 **Screw Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard 2nd material response **Screw Surface Treatment:** Aluminum **Screw Surface Treatment Specification:** Mil-c-83488, type 2 cl 3 military specification single treatment response **Thread Series Designator:** 

Unjf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A500d0

## NSN 5305-01-129-4432

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.