NSN 5305-01-129-6934

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-129-6934

3a Thread Direction: Right-hand Thread Length: Between 0.505 inches and 0.572 inches Fastener Length: Between 1.765 inches and 1.812 inches Head Style: Flat countersunk undercut Head Diameter: Between 0.629 inches and 0.634 inches Head Height: Between 0.828 inches and 0.030 inches Grip Diameter: Between 0.8115 inches and 0.3120 inches Internal Drive Style: High-torque Thread Diameter: 0.312 inches Grip Dameter: 0.312 inches Between 0.3115 inches and 1.260 inches Thread Diameter: 0.312 inches Between 1.240 inches and 1.260 inches Thready Oty Per Inch (tpi): 24 Countersink Angle: 10.0.0 degrees Special Features: Furnish with one o ring Material Naterial Specification: Naterial Specification: Naterial Specification: Naterial Specification: Naterial Specification: <	Thread Class:
Right-hand Firead Length: Between 0.505 inches and 0.572 inches Fastener Length: Between 1.765 inches and 1.812 inches Head Style: Flat countersunk undercut Head Diameter: Between 0.629 inches and 0.634 inches Head Height: Between 0.088 inches and 0.090 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Internal Drive Style: High-torque Thread Diameter: 0.312 inches Grip Dameter: 0.312 inches Patween 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): 24 Countersink Angle: 10.0.0 degrees Surface Finish: 32.0 microinches threads Special Features: Furnish with one o ring Material: Thread Specification: Nas621 assn standard single material response Thread Series Designator: Unif Shelf Life: Na Durit Of Measure: Thread Series Designator: <th>3a</th>	3a
Tread Length: Between 0.505 inches and 0.572 inches Fastener Length: Between 1.765 inches and 1.812 inches Head Style: Flat countersunk undercut Head Diameter: Between 0.629 inches and 0.634 inches Head Height: Between 0.088 inches and 0.090 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Internal Drive Style: High-torque Thread Diameter: 0.312 inches Between 1.240 inches and 1.260 inches Thready Day Per Inch (tpi): 24 Countersink Angle: 10.0.0 degrees Surface Finish: 32.0 microinches threads Special Features: Furail Specification: Nas621 assn standard single material response Thread Steries Designator: Unif Na Dirtlife: Na Dirtlife: Na Dirtlife: Nateriat Formation and single material response Hird Measure: Na	Thread Direction:
Between 0.505 inches and 0.572 inches Fastener Length: Between 1.765 inches and 1.812 inches Head Style: Flat countersunk undercut Head Diameter: Between 0.629 inches and 0.634 inches Head Height: Between 0.088 inches and 0.090 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Internal Drive Style: High-torque Thread Diameter: 0.312 inches Grip Length: Between 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): 24 Countersink Angle: 10.0.0 degrees Surface Finish: 32.0 microinches threads Special Features: Furnish with one o ring Material: Titanium alloy uns r54520 Material Specification: Nas621 assn standard single material response Thread Stries Designator: Unif Shelf Life: N/a Unif Of Measure: Tread Stries Designator: Dirief Of Measure: N/a <th>Right-hand</th>	Right-hand
Fastener Length: Between 1.765 inches and 1.812 inches Head Style: Flat countersunk undercut Head Diameter: Between 0.629 inches and 0.634 inches Head Height: Between 0.088 inches and 0.090 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Internal Drive Style: High-torque Thread Diameter: 0.312 inches Grip Length: Between 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): 24 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Special Features: Furnish with one o ring Material: Thread Series Designator: Unif Shelf Life: Iva Va Unif Demilitarization:	Thread Length:
Between 1.76 inches and 1.812 inches Head Style: Flat countersunk undercut Head Diameter: Between 0.629 inches and 0.634 inches Head Height: Between 0.688 inches and 0.090 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Internal Drive Style: High-torque Thread Diameter: 0.312 inches Grip Length: Between 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): 24 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Special Features: Furnish with one o ring Material: Thread Specification: Nas621 assn standard single material response Thread Specification: Unif Sheff Liffe: Va	Between 0.505 inches and 0.572 inches
Head Style: Flat countersunk undercut Head Diameter: Between 0.629 inches and 0.634 inches Head Height: Between 0.088 inches and 0.090 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Internal Drive Style: High-torque Thread Diameter: 0.312 inches Grip Length: Between 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): 24 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Special Features: Furnish with one o ring Material: Titanium alloy uns r54520 Material Specification: Nas621 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demillitarization:	Fastener Length:
Flat countersumk undercut Head Diameter: Between 0.629 inches and 0.634 inches Head Height: Between 0.088 inches and 0.090 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Internal Drive Style: High-torque Thread Diameter: 0.312 inches Grip Length: Between 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): 24 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Special Features: Fursih with one or ring Material: Nas621 asen standard single material response Thread Specification: Nas621 asen standard single material response Intre Vai Vai Dird Measure: Via Dird Measure: Into f Measure:	Between 1.765 inches and 1.812 inches
Head Diameter: Between 0.629 inches and 0.634 inches Head Height: Between 0.088 inches and 0.090 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Internal Drive Style: High-torque Thread Diameter: 0.312 inches Grip Length: Between 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): 24 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Special Features: Furnish with one o ring Material: Nas621 assn standard single material response Thread Series Designator: Unif Shef Life: N/a Dunif Of Measure: To Dunif Of Measure: To Dunif Of Measure: To Dunif Uter Dunif Uter Dunif Uter Dunif Of Measure: To Dunif Uter Dunif Uter Dunif Uter	Head Style:
Between 0.629 inches and 0.634 inches Head Height: Between 0.088 inches and 0.090 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Internal Drive Style: High-torque Thread Diameter: 0.312 inches Grip Length: Between 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): 24 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Special Features: Furnish with one o ring Material: Titanium alloy uns r54520 Material Specification: Nas621 assn standard single material response Thread Series Designator: Unif Shelf Life: N/a Unif Of Measure: Demilitarization:	Flat countersunk undercut
Head Height: Between 0.088 inches and 0.090 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Internal Drive Style: High-torque Thread Diameter: 0.312 inches Grip Length: Between 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): 24 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Special Features: Furnish with one o ring Material: Titanium alloy uns r54520 Material Specification: Nas621 assn standard single material response Thread Series Designator: Unif Shelf Life: N/a Unif Of Measure: 	Head Diameter:
Between 0.088 inches and 0.090 inches Grip Diameter: Between 0.3115 inches and 0.3120 inches Internal Drive Style: High-torque Thread Diameter: 0.312 inches Grip Length: Between 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): 24 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Special Features: Furnish with one o ring Material: Titanium alloy uns r54520 Material Specification: Nas621 assn standard single material response Thread Series Designator: Unif Shelf Life: N/a Unit Of Measure: - Demilitarization:	Between 0.629 inches and 0.634 inches
Grip Diameter: Between 0.3115 inches and 0.3120 inches Internal Drive Style: High-torque Thread Diameter: 0.312 inches Grip Length: Between 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): 24 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Special Features: Furnish with one o ring Material: Titanium alloy uns r54520 Material Specification: Nas621 assn standard single material response Thread Series Designator: Unif Shelf Life: N/a Unit Of Measure: 	Head Height:
Between 0.3115 inches and 0.3120 inches Internal Drive Style: High-torque Thread Diameter: 0.312 inches Grip Length: Between 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): 24 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Special Features: Furnish with one o ring Material: Titanium alloy uns r54520 Material Specification: Nas621 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:	Between 0.088 inches and 0.090 inches
Internal Drive Style: High-torque Thread Diameter: 0.312 inches Grip Length: Between 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): 24 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Special Features: Furnish with one o ring Material: Titanium alloy uns r54520 Material Specification: Nas621 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: 	Grip Diameter:
High-torque Thread Diameter: 0.312 inches Grip Length: Between 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): 24 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Special Features: Furnish with one o ring Material: Titanium alloy uns r54520 Material Specification: Nas621 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure:	Between 0.3115 inches and 0.3120 inches
Thread Diameter: 0.312 inches Grip Length: Between 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): 24 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Special Features: Furnish with one o ring Material: Titanium alloy uns r54520 Material Specification: Nas621 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:	Internal Drive Style:
0.312 inches Grip Length: Between 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): 24 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Special Features: Furnish with one o ring Material: Titanium alloy uns r54520 Material Specification: Nas621 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: 	High-torque
Grip Length: Between 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): 24 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Special Features: Furnish with one o ring Material: Titanium alloy uns r54520 Material Specification: Nas621 assn standard single material response Thread Series Designator: Unif Shelf Life: N/a Unit Of Measure: 	Thread Diameter:
Between 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): 24 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Special Features: Furnish with one o ring Material: Titanium alloy uns r54520 Material Specification: Nas621 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:	0.312 inches
Thready Qty Per Inch (tpi): 24 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Special Features: Furnish with one o ring Material: Titanium alloy uns r54520 Material Specification: Nas621 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: 	Grip Length:
24 Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Special Features: Furnish with one o ring Material: Titanium alloy uns r54520 Material Specification: Nas621 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: 	Between 1.240 inches and 1.260 inches
Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches threads Special Features: Furnish with one o ring Material: Titanium alloy uns r54520 Material Specification: Nas621 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: 	Thready Qty Per Inch (tpi):
100.0 degrees Surface Finish: 32.0 microinches threads Special Features: Furnish with one o ring Material: Titanium alloy uns r54520 Material Specification: Nas621 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:	24
Surface Finish: 32.0 microinches threads Special Features: Furnish with one o ring Material: Titanium alloy uns r54520 Material Specification: Nas621 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: 	Countersink Angle:
32.0 microinches threads Special Features: Furnish with one o ring Material: Titanium alloy uns r54520 Material Specification: Nas621 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:	100.0 degrees
Special Features: Furnish with one o ring Material: Titanium alloy uns r54520 Material Specification: Nas621 assn standard single material response Thread Series Designator: Unif Shelf Life: N/a Unit Of Measure: 	Surface Finish:
Furnish with one o ring Material: Titanium alloy uns r54520 Material Specification: Nas621 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: 	32.0 microinches threads
Material: Titanium alloy uns r54520 Material Specification: Nas621 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: 	Special Features:
Titanium alloy uns r54520 Material Specification: Nas621 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:	Furnish with one o ring
Material Specification: Nas621 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:	Material:
Nas621 assn standard single material response Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:	Titanium alloy uns r54520
Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:	Material Specification:
Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:	Nas621 assn standard single material response
Shelf Life: N/a Unit Of Measure: Demilitarization:	Thread Series Designator:
N/a Unit Of Measure: Demilitarization:	Unjf
Unit Of Measure: Demilitarization:	Shelf Life:
 Demilitarization:	N/a
	Unit Of Measure:
No	Demilitarization:
	No

NSN 5305-01-129-6934

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

