NSN 5305-01-129-9034

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-129-9034 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.188 inches and 0.218 inches **Fastener Length:** Between 0.583 inches and 0.613 inches **Head Style:** Pan **Head Diameter:** Between 0.305 inches and 0.315 inches **Head Height:** Between 0.077 inches and 0.107 inches **Internal Drive Style:** Cross recess type 1 **Material Accommodated Thickness:** Between 0.063 inches and 0.125 inches **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 112000 pounds per square inch Material: Steel comp 304 stand-off **Material Specification:** Mil-s-5059 military specification single material response primary washer **Surface Treatment:** Passivate stand-off **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response stand-off **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**



NSN 5305-01-129-9034

Panel Screw Assembly - Page 2 of 2



Mil-std (military Standard):

Mil-s-23195 spec.