## NSN 5305-01-129-9060

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-129-9060 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.631 inches and 0.698 inches **Fastener Length:** Between 1.453 inches and 1.500 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.881 inches and 0.888 inches **Head Height:** Between 0.130 inches and 0.133 inches **Grip Diameter:** Between 0.4365 inches and 0.4370 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.438 inches **Grip Length:** Between 0.802 inches and 0.822 inches Thready Qty Per Inch (tpi): 20 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads **Special Features:** Furnished with one oring Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unjf Shelf Life:

N/a **Unit Of Measure:** 

## NSN 5305-01-129-9060

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0