## NSN 5305-01-130-4261

**Thread Class:** 

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-130-4261

3a						
Thread Direction:						
Right-hand						
Thread Length:						
Between 0.245 inches and 0.375 inches						
Fastener Length:						
Between 0.345 inches and 0.375 inches						
Head Style:						
Flat chamfer						
Head Diameter:						
Between 0.365 inches and 0.375 inches						
Head Height:						
Between 0.244 inches and 0.250 inches						
Internal Drive Style:						
Hexagon						
Thread Diameter:						
0.250 inches						
Width Across Flats:						
Between 0.1875 inches and 0.1900 inches						
Thready Qty Per Inch (tpi):						
20						
Min. Tensile Strength (psi):						
80000 pounds per square inch						
Hardness Rating:						
80.0 rockwell c						
Minimum Yield Strength:						
30000 pounds per square inch						
Material:						
Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384						
Material Specification:						
66 federal standard all material responses						
Surface Treatment:						
Cadmium and chromate						
Surface Treatment Specification:						
Qq-p-416, type 2, cl 2 federal specification single treatment response						
Thread Series Designator:						
Unrc						
Specification Data:						
80205-nas1352 professional/industrial association standard						
Shelf Life:						
N/a						

## NSN 5305-01-130-4261

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0