NSN 5305-01-130-6555Machine Screw - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5305-01-130-6555
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.545 inches and 0.624 inches
Fastener Length:
Between 0.609 inches and 0.656 inches
Head Style:
Hexagon
Head Height:
Between 0.105 inches and 0.120 inches
Width Between Flats:
Between 0.305 inches and 0.314 inches
Hole Diameter:
Between 0.046 inches and 0.056 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Hole Quantity:
3
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Product Name:
Navy special project
Screw Material:
Steel comp e4340 or steel comp 8740
Screw Material Specification:
Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard
2nd material response
Screw Surface Treatment:
Aluminum
Screw Surface Treatment Specification:
Mil-c-83488, type 2 cl 3 military specification single treatment response
Head Hole Configuration Style:
Hexagon corners
Thread Series Designator:
Unjf
Shelf Life:

NSN 5305-01-130-6555

Machine Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5000 spec.