

View Online at <https://aerobasegroup.com/nsn/5305-01-130-9019>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.338 inches and 0.388 inches

**Fastener Length:**

Between 0.473 inches and 0.503 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.339 inches and 0.381 inches

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.115 inches and 0.135 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

32.0 microinches threads

**Special Features:**

Internal drive ribbed

**Material:**

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 4340

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, ty2, cl2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1580 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0