## NSN 5305-01-130-9024



Panel Screw Assembly - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-130-9024 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.140 inches and 0.150 inches **Fastener Length:** Between 0.375 inches and 0.405 inches **Head Style:** Pan **Head Diameter:** 0.365 inches **Head Height:** Between 0.087 inches and 0.097 inches **Material Accommodated Thickness:** Between 0.060 inches and 0.070 inches **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 302b or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385 **Material Specification:** Qq-w-423 cond b federal specification single material response spring **Surface Treatment:** Passivate stand-off **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response stand-off **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

Fiig: A003b0

No

**Demilitarization:**