NSN 5305-01-131-2202

Thread Class:

За

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-131-2202

Thread Direction: Right-hand Thread Length: Between 0.251 inches and 0.301 inches **Fastener Length:** Between 0.699 inches and 0.729 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.306 inches and 0.313 inches **Head Height:** Between 0.103 inches and 0.118 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1123 professional/industrial association standard Shelf Life:

N/a

NSN 5305-01-131-2202

Close Tolerance Screw - Page 2 of 2



| ш | ın | 10 | <i>(</i>)+ | Measure: | |
|---|----|----|-------------|----------|--|
| | | | | | |

--

Demilitarization:

No

Fiig:

A003b0