## NSN 5305-01-131-2916

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-131-2916 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 2.000 inches **Fastener Length:** Between 3.420 inches and 3.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 1.107 inches and 1.125 inches **Head Height:** Between 0.740 inches and 0.750 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.750 inches Width Across Flats: Between 0.625 inches and 0.631 inches Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 class 2 federal specification single treatment response **Thread Series Designator:** Unrf **Specification Data:** 80205-nas1351 professional/industrial association standard Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-01-131-2916

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0