NSN 5305-01-131-2919

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-131-2919

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.220 inches and 0.375 inches
Fastener Length:
Between 0.345 inches and 0.375 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.550 inches and 0.562 inches
Head Height:
Between 0.368 inches and 0.375 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.375 inches
Width Across Flats:
Between 0.3125 inches and 0.3160 inches
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell c
Minimum Yield Strength:
30000 pounds per square inch
Material:
Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384
Material Specification:
66 federal standard all material responses
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, ty1, cl2 federal specification single treatment response
Thread Series Designator:
Unrc
Specification Data:
80205-nas1352 professional/industrial association standard
Shelf Life:
N/a

NSN 5305-01-131-2919

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0