Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-131-2920



# **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 1.648 inches and 1.750 inches Fastener Length: Between 1.710 inches and 1.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.1094 inches and 0.1111 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c **Minimum Yield Strength:** 155000 pounds per square inch

Material:

Steel

Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416, ty2, cl2 federal specification single treatment response

#### **Thread Series Designator:**

Unrc

Specification Data:

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

### Unit Of Measure:

--

# NSN 5305-01-131-2920

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

