
NSN 5305-01-131-2935

Close Tolerance Screw - Page 1 of 2





| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.378 inches and 0.428 inches |
| Fastener Length: |
| Between 0.763 inches and 0.793 inches |
| Head Style: |
| Pan no. 2 |
| Head Diameter: |
| Between 0.477 inches and 0.492 inches |
| Head Height: |
| Between 0.140 inches and 0.150 inches |
| Grip Diameter: |
| Between 0.2485 inches and 0.2495 inches |
| Internal Drive Style: |
| High-torque |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| Between 0.365 inches and 0.385 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Titanium alloy |
| Material Specification: |
| Nas621 assn standard single material response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas1578 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| |

No

NSN 5305-01-131-2935

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

