NSN 5305-01-131-8456

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-131-8456 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.750 inches **Fastener Length:** Between 4.938 inches and 5.000 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.319 inches and 0.332 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 4037 or steel comp 8630 **Screw Material Specification:** Ams6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, ty1, cl2 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas514 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-131-8456

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.