

View Online at <https://aerobasegroup.com/nsn/5305-01-131-9824>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.487 inches and 0.577 inches

**Fastener Length:**

Between 0.594 inches and 0.625 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.175 inches and 0.199 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.099 inches

**Thready Qty Per Inch (tpi):**

48

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Countersink Angle:**

Between 80.0 degrees and 82.0 degrees

**Screw Material:**

Steel comp 302 or steel comp 430 or steel comp 303

**Screw Material Specification:**

Qq-s-763 federal specification 1st material response or qq-s-763 federal specification 2nd material response or astma582 assn standard 3rd material response

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Specification Or Standard:**

1 type and 2s style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0