## NSN 5305-01-132-0511

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-132-0511 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.351 inches and 0.371 inches **Fastener Length:** Between 1.552 inches and 1.572 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.502 inches and 0.507 inches **Grip Diameter:** Between 0.2487 inches and 0.2492 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.086 inches first hole **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.062 inches and 1.078 inches Width Across Flats: 0.250 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** 100.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 1.453 inches first hole **Surface Finish:** 63.0 microinches grip **Special Features:** Furnished with one positive locking ring Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment:** 

Passivate

**Thread Series Designator:** 

Unjf

## NSN 5305-01-132-0511

Close Tolerance Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0