NSN 5305-01-132-0512

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-132-0512 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.344 inches and 0.395 inches **Fastener Length:** Between 4.490 inches and 4.510 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.502 inches and 0.507 inches **Grip Diameter:** Between 0.2487 inches and 0.2492 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.086 inches first hole **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches **Grip Length:** Between 4.000 inches and 4.016 inches Width Across Flats: 0.250 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** 100.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 4.391 inches first hole **Surface Finish:** 63.0 microinches grip **Special Features:** Retaining element in shank Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response

Surface Treatment: Passivate

Thread Series Designator:

Unjf

NSN 5305-01-132-0512

Close Tolerance Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0