## NSN 5305-01-132-2154

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-132-2154 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.200 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Fillister **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **First Diameter From Head:** Between 0.115 inches and 0.135 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.300 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 321 **Material Specification:** Qq-s-763 federal specification all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 type 2 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5305-01-132-2154

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0