

View Online at <https://aerobasegroup.com/nsn/5305-01-132-2159>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.507 inches and 0.620 inches

Fastener Length:

Between 0.590 inches and 0.620 inches

Head Style:

Pan

Head Diameter:

Between 0.716 inches and 0.740 inches

Head Height:

Between 0.244 inches and 0.261 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

55000 pounds per square inch

Screw Material:

Copper alloy 268 or copper alloy 230 or copper alloy 377 or copper alloy 360 or copper alloy 353 or copper alloy 270 or copper alloy 462 or copper alloy 464 or copper alloy 482 or copper alloy 485 or copper alloy 210 or copper alloy 220 or copper alloy 510 or copper alloy 745 or copper alloy 752 or copper alloy 757 or copper alloy 764 or copper alloy 770 or copper alloy 342

Screw Surface Treatment:

Oxide

Screw Surface Treatment Specification:

Mil-f-495 military specification single treatment response

Color:

Black

Thread Series Designator:

Unf

Specification Or Standard:

3 type and 9c style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-f-495 spec.