

View Online at <https://aerobasegroup.com/nsn/5305-01-132-2166>

Fastener Length:

Between 0.825 inches and 0.875 inches

Head Style:

Hexagon extended washer

Head Height:

Between 0.202 inches and 0.240 inches

Width Between Flats:

Between 0.367 inches and 0.375 inches

Extended Washer Diameter:

Between 0.480 inches and 0.520 inches

Extended Washer Thickness:

Between 0.030 inches and 0.050 inches

Internal Drive Style:

W/o internal drive

Features Provided:

Casehardened

Min. Tensile Strength (psi):

150000 pounds per square inch

Hardness Rating:

32.0 rockwell c and 38.0 rockwell c

Nonmachine Thread Style:

Blunt (type tt)

Nonmachine Thread Diameter:

0.250 inches

Material:

Steel comp 4037

Material Specification:

66 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, ty2, cl2 federal specification single treatment response or mil-c-81562, ty2, cl2 military specification single treatment response

Specification Or Standard:

Tt type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-c-81562 spec.