## NSN 5305-01-132-3361

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-132-3361 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.150 inches and 0.198 inches **Fastener Length:** Between 0.178 inches and 0.198 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.130 inches and 0.142 inches **Head Height:** Between 0.038 inches and 0.046 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.073 inches Thready Qty Per Inch (tpi): 72 Min. Tensile Strength (psi): 70000 pounds per square inch **Hardness Rating:** Between 80.0 rockwell b and 85.0 rockwell b **Screw Material:** Steel comp 303 **Screw Material Specification:** Astm a582 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Mil-t-704 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A500d0

## NSN 5305-01-132-3361

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-t-704 spec.