
## NSN 5305-01-132-3386

Close Tolerance Screw - Page 1 of 2

3a





## **Thread Class: Thread Direction: Right-hand Thread Length:** Between 0.338 inches and 0.388 inches Fastener Length: Between 1.598 inches and 1.628 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.360 inches and 0.374 inches **Head Height:** Between 0.115 inches and 0.125 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches Grip Length: Between 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 or steel comp 8735 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1578 professional/industrial association standard Shelf Life:

N/a

32

## NSN 5305-01-132-3386

Close Tolerance Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

