NSN 5305-01-132-5284

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-132-5284

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.401 inches and 0.451 inches
Fastener Length:
Between 1.723 inches and 1.753 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.464 inches and 0.507 inches
Grip Diameter:
Between 0.2490 inches and 0.2495 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.250 inches
Grip Length:
Between 1.302 inches and 1.322 inches
Thready Qty Per Inch (tpi):
28 Min Tancila Strength (noi):
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees Surface Finish:
32.0 microinches threads
Material:
Titanium alloy
Material Specification:
Nas 621 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
80205-nas664 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5305-01-132-5284

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

