NSN 5305-01-132-5768

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-132-5768 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.490 inches and 0.510 inches **Fastener Length:** Between 1.063 inches and 1.125 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **First Diameter From Head:** Between 0.115 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.573 inches and 0.615 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 60000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel comp 1010 or steel comp 1011 **Material Specification:** Fed standard 66 federal standard all material responses **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-01-132-5768

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0