## NSN 5305-01-132-6508

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-132-6508 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.506 inches and 0.556 inches **Fastener Length:** Between 1.391 inches and 1.421 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.625 inches and 0.635 inches **Grip Diameter:** Between 0.3115 inches and 0.3120 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.865 inches and 0.885 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** The dimensions given for mrc "aasl" head diameter are theoretical Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5305-01-132-6508

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0