## NSN 5305-01-132-9792

Machine Screw - Page 1 of 2

**Thread Class:** 

3a

32

--

No

View Online at https://aerobasegroup.com/nsn/5305-01-132-9792



## **Thread Direction: Right-hand Thread Length:** 0.280 inches Fastener Length: Between 0.296 inches and 0.343 inches **Head Style:** Hexagon **Head Height:** Between 0.080 inches and 0.093 inches Width Between Flats: Between 0.243 inches and 0.251 inches Internal Drive Style: Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Steel comp e4340 or steel comp 8740 **Screw Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 military specification 2nd material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1801 professional/industrial association standard Shelf Life: N/a Unit Of Measure: **Demilitarization:** Fiig: A500d0

## NSN 5305-01-132-9792

Machine Screw - Page 2 of 2

## Mil-std (military Standard):

Mil-s-5000 spec.

