NSN 5305-01-133-0181

Close Tolerance Screw - Page 1 of 2



| view Online at https://aerobasegroup.com/nsr//5505-01-155-0161 |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.338 inches and 0.388 inches |
| Fastener Length: |
| Between 1.473 inches and 1.503 inches |
| Head Style: |
| Pan no. 2 |
| Head Diameter: |
| Between 0.360 inches and 0.374 inches |
| Head Height: |
| Between 0.115 inches and 0.125 inches |
| Grip Diameter: |
| Between 0.1885 inches and 0.1895 inches |
| Internal Drive Style: |
| High-torque |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 1.115 inches and 1.135 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single |
| material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas1578 professional/industrial association standard |

N/a

Shelf Life:

NSN 5305-01-133-0181

Close Tolerance Screw - Page 2 of 2



| | | eas | |
|--|--|-----|--|

--

Demilitarization:

No

Fiig:

A003b0