NSN 5305-01-133-2174

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-133-2174 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.359 inches and 0.391 inches **Fastener Length:** Between 0.922 inches and 0.954 inches **Head Style:** Knurled no. 4 **Head Diameter:** Between 0.557 inches and 0.567 inches **Head Height:** Between 0.234 inches and 0.266 inches **First Diameter From Head:** Between 0.170 inches and 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.553 inches and 0.573 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Straight knurl Material: Steel comp 203ez or steel comp 303 or steel comp 303se or steel comp 303ma or steel comp 303cu or steel comp 303 plus x or steel comp 416 or steel comp 416se or steel comp 416 plus x or steel comp 430f or steel comp m1020 **Material Specification:** Astm a581 assn standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf

N/a

Shelf Life:

Unit Of Measure:

NSN 5305-01-133-2174

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0