NSN 5305-01-133-2179

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-133-2179 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.900 inches and 1.000 inches **Fastener Length:** 1.000 inches **Head Style:** Hexagon **Head Height:** Between 0.172 inches and 0.190 inches Width Between Flats: Between 0.367 inches and 0.375 inches Washer Quantity: **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 120000 pounds per square inch Hardness Rating: 23.0 rockwell c and 40.0 rockwell c **Primary Washer Outside Diameter:** Between 0.495 inches and 0.515 inches **Primary Washer Style:** Flat **Primary Washer Material Thickness:** Between 0.056 inches and 0.071 inches Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unc

Shelf Life:

N/a

NSN 5305-01-133-2179

Assembled Washer Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0