## NSN 5305-01-133-4461

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-133-4461

view Online at https://aerobasegroup.com/nsn/5305-01-133-4461	
Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.887 inches and 1.000 inches	
Fastener Length:	
Between 0.970 inches and 1.000 inches	
Head Style:	
Flat chamfer	
Head Diameter:	
Between 0.457 inches and 0.469 inches	
Head Height:	
Between 0.306 inches and 0.312 inches	
Locking Feature:	
Strip threads	
Internal Drive Style:	
Hexagon	
Thread Diameter:	
0.312 inches	
Width Across Flats:	
Between 0.2500 inches and 0.2530 inches	
Thready Qty Per Inch (tpi):	
24	
Min. Tensile Strength (psi):	
170000 pounds per square inch	
Hardness Rating:	
38.0 rockwell c and 45.0 rockwell c	
Minimum Yield Strength:	
150000 pounds per square inch	
Material:	
Steel fastener	
Surface Treatment:	
Cadmium fastener and chromate fastener	
Surface Treatment Specification:	
Qq-p-416, type 2 class 2 federal specification single treatment response fastener	
Thread Series Designator:	
Unrf	
Specification Data:	
80205-nas1351 professional/industrial association standard	
Shelf Life:	
N/a	

N/a

## NSN 5305-01-133-4461

Socket Head Cap Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0