

View Online at <https://aerobasegroup.com/nsn/5305-01-133-7184>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.219 inches and 0.312 inches

Fastener Length:

Between 0.281 inches and 0.312 inches

Head Style:

Binding

Head Diameter:

Between 0.275 inches and 0.290 inches

Head Height:

Between 0.071 inches and 0.087 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

125000 pounds per square inch

Screw Material:

Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 403 or steel comp 405 or steel comp 410 or steel comp 414 or steel comp 420 or steel comp 430 or steel comp 440a or steel comp 440b or steel comp 440c or steel comp 446

Screw Material Specification:

Qq-s-763 federal specification all material responses

Screw Surface Treatment:

Passivate

Screw Surface Treatment Specification:

3608009 fscm 27914 mfr ref single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0