

View Online at <https://aerobasegroup.com/nsn/5305-01-133-9442>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.400 inches and 0.450 inches

Fastener Length:

Between 1.222 inches and 1.252 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.464 inches and 0.506 inches

Grip Diameter:

Between 0.2485 inches and 0.2495 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Internal Drive Style:

High-torque

Thread Diameter:

0.250 inches

Grip Length:

Between 0.802 inches and 0.822 inches

Thready Qty Per Inch (tpi):

28

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.096 inches first hole and 1.146 inches first hole

Surface Finish:

32.0 microinches threads

Material:

Steel comp 8740

Material Specification:

Mil-s-6049 military specification single material response

Surface Treatment:

Aluminum and chromate

Surface Treatment Specification:

Mil-c-83488, type 2, cl 3 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.