## NSN 5305-01-134-0193

Machine Screw - Page 1 of 2

**Thread Class:** 

3a

View Online at https://aerobasegroup.com/nsn/5305-01-134-0193



## **Thread Direction: Right-hand Thread Length:** Between 0.548 inches and 0.625 inches Fastener Length: Between 1.157 inches and 1.204 inches **Head Style:** Pan **Head Diameter:** Between 0.594 inches and 0.615 inches **Head Height:** Between 0.203 inches and 0.218 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c **Screw Material:** Steel comp 4037 or steel comp 8630 **Screw Material Specification:** Ams6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, ty2, cl3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A500d0

## NSN 5305-01-134-0193

Machine Screw - Page 2 of 2

## Mil-std (military Standard):

Mil-s-6050 spec.

