NSN 5305-01-134-0194

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-134-0194

| Thread Class: |
|---------------------------------------------------------------------------------------------------------|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.365 inches and 0.447 inches |
| Fastener Length: |
| Between 1.531 inches and 1.593 inches |
| Head Style: |
| Pan |
| Head Diameter: |
| 0.375 inches |
| Head Height: |
| Between 0.089 inches and 0.099 inches |
| Washer Quantity: |
| 1 |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.190 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Primary Washer Outside Diameter: |
| 0.437 inches |
| Primary Washer Style: |
| Flat |
| Primary Washer Material Thickness: |
| Between 0.025 inches and 0.030 inches |
| Material: |
| Steel comp 8630 or steel comp 4037 |
| Material Specification: |
| Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, ty2, cl3 federal specification single treatment response |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5305-01-134-0194

Assembled Washer Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6050 spec.