NSN 5305-01-134-1973

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-134-1973

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.755 inches and 0.822 inches
Fastener Length:
Between 5.203 inches and 5.250 inches
Head Style:
Flat countersunk
Head Diameter:
Between 1.007 inches and 1.017 inches
Grip Diameter:
Between 0.4982 inches and 0.4991 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.500 inches
Grip Length:
Between 4.428 inches and 4.448 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
36.0 rockwell c and 40.0 rockwell c Countersink Angle:
Countersink Angle:
Countersink Angle: 100.0 degrees
Countersink Angle: 100.0 degrees Surface Finish:
Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches grip
Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches grip Material:
Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate
Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification:
Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate
Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification:
Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2 class 2 federal specification single treatment response Thread Series Designator: Unjf
Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2 class 2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:
Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2 class 2 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas338 professional/industrial association standard
Countersink Angle: 100.0 degrees Surface Finish: 32.0 microinches grip Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2 class 2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:

N/a

NSN 5305-01-134-1973

Close Tolerance Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0