## NSN 5305-01-134-3275

Panel Screw Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-134-3275

| view Online at https://aeiobasegroup.com/hsi//5505-01-154-5275    |
|---|
| Thread Class:   |
| 2a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| 0.250 inches  |
| Fastener Length:  |
| Between 0.547 inches and 0.577 inches                             |
| Head Style:   |
| Flat countersunk  |
| Head Diameter:  |
| 0.320 inches  |
| Material Accommodated Thickness:                                  |
| Between 0.050 inches and 0.080 inches                             |
| Thread Diameter:  |
| 0.164 inches  |
| Thready Qty Per Inch (tpi):                                       |
| 32  |
| Countersink Angle:  |
| 100.0 degrees   |
| Material:   |
| Steel comp 303 stand-off or steel comp 303se stand-off            |
| Material Specification:   |
| Astm a493 assn standard all material responses fastener           |
| Surface Treatment:  |
| Passivate stand-off   |
| Surface Treatment Specification:                                  |
| Qq-p-35 federal specification single treatment response stand-off |
| Thread Series Designator:   |
| Unc   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A003b0  |
|   |
|   |