NSN 5305-01-134-5749



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-134-5749 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.095 inches **Fastener Length:** 0.310 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.265 inches and 0.275 inches **Head Height:** 0.075 inches **Shoulder Diameter:** 0.195 inches first shoulder and 0.205 inches first shoulder **Shoulder Length:** 0.105 inches first shoulder and 0.115 inches first shoulder **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Shoulder Shape:** Round first shoulder Material: Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 **Material Specification:** Qq-s-763 federal specification all material responses **Surface Treatment: Passivate Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

NSN 5305-01-134-5749

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0