

View Online at <https://aerobasegroup.com/nsn/5305-01-134-9361>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.482 inches and 0.561 inches

**Fastener Length:**

Between 0.546 inches and 0.593 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.125 inches and 0.140 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Hole Diameter:**

Between 0.046 inches and 0.056 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.250 inches

**Hole Quantity:**

3

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Screw Material:**

Steel comp e4340 or steel comp 8740

**Screw Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard 2nd material response

**Screw Surface Treatment:**

Aluminum

**Screw Surface Treatment Specification:**

Mil-c-83488, type 2 cl 3 military specification single treatment response

**Head Hole Configuration Style:**

Hexagon corners

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0

**Mil-std (military Standard):**

Mil-s-5000 spec.