## NSN 5305-01-134-9363

Machine Screw - Page 1 of 2

**Thread Class:** 

3a

View Online at https://aerobasegroup.com/nsn/5305-01-134-9363



## **Thread Direction: Right-hand Thread Length:** Between 1.295 inches and 1.374 inches Fastener Length: Between 1.359 inches and 1.406 inches **Head Style:** Hexagon **Head Height:** Between 0.125 inches and 0.140 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c **Product Name:** Navy special project **Screw Material:** Steel comp e4340 or steel comp 8740 **Screw Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:**

80205-nas1801 professional/industrial association standard

Shelf Life:

N/a

## Unit Of Measure:

## NSN 5305-01-134-9363

Machine Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5000 spec.

