NSN 5305-01-135-0113

Shoulder Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-135-0113



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.381 inches and 0.431 inches Fastener Length: Between 1.703 inches and 1.733 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.339 inches and 0.381 inches Shoulder Diameter: 0.202 inches first shoulder and 0.203 inches first shoulder Shoulder Length: 1.228 inches first shoulder and 1.248 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder Material: Steel comp 8735 or steel comp 8740 or steel comp e4340 or steel comp 4140 or steel comp 6150 or steel comp 4130 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1703 professional/industrial association standard

Shelf Life:

N/a

NSN 5305-01-135-0113

Shoulder Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

