Externally Relieved Body Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-135-0796

Thread Class: 2a Thread Direction: Right-hand Thread Length: 0.188 inches Fastener Length: Between 0.969 inches and 1.000 inches Head Style: Pan Head Diameter: Between 0.256 inches and 0.270 inches Head Height: Between 0.087 inches and 0.097 inches First Diameter From Head: Between 0.100 inches and 0.104 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.797 inches
Thread Direction:Right-handThread Length:0.188 inchesFastener Length:Between 0.969 inches and 1.000 inchesHead Style:PanHead Diameter:Between 0.256 inches and 0.270 inchesHead Height:Between 0.087 inches and 0.097 inchesFirst Diameter From Head:Between 0.100 inches and 0.104 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.797 inchesInternal Drive Style:
Right-handThread Length:0.188 inchesFastener Length:Between 0.969 inches and 1.000 inchesHead Style:PanHead Diameter:Between 0.256 inches and 0.270 inchesHead Height:Between 0.087 inches and 0.097 inchesFirst Diameter From Head:Between 0.100 inches and 0.104 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.797 inchesInternal Drive Style:
Thread Length:0.188 inchesFastener Length:Between 0.969 inches and 1.000 inchesHead Style:PanHead Diameter:Between 0.256 inches and 0.270 inchesHead Height:Between 0.087 inches and 0.097 inchesFirst Diameter From Head:Between 0.100 inches and 0.104 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.797 inchesInternal Drive Style:
0.188 inches Fastener Length: Between 0.969 inches and 1.000 inches Head Style: Pan Head Diameter: Between 0.256 inches and 0.270 inches Head Height: Between 0.087 inches and 0.097 inches First Diameter From Head: Between 0.100 inches and 0.104 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.797 inches
Fastener Length:Between 0.969 inches and 1.000 inchesHead Style:PanHead Diameter:Between 0.256 inches and 0.270 inchesHead Height:Between 0.087 inches and 0.097 inchesFirst Diameter From Head:Between 0.100 inches and 0.104 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.797 inchesInternal Drive Style:
Between 0.969 inches and 1.000 inchesHead Style:PanHead Diameter:Between 0.256 inches and 0.270 inchesHead Height:Between 0.087 inches and 0.097 inchesFirst Diameter From Head:Between 0.100 inches and 0.104 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.797 inchesInternal Drive Style:
Head Style:PanHead Diameter:Between 0.256 inches and 0.270 inchesHead Height:Between 0.087 inches and 0.097 inchesFirst Diameter From Head:Between 0.100 inches and 0.104 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.797 inchesInternal Drive Style:
Pan Head Diameter: Between 0.256 inches and 0.270 inches Head Height: Between 0.087 inches and 0.097 inches First Diameter From Head: Between 0.100 inches and 0.104 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.797 inches
Head Diameter: Between 0.256 inches and 0.270 inches Head Height: Between 0.087 inches and 0.097 inches First Diameter From Head: Between 0.100 inches and 0.104 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.797 inches Internal Drive Style:
Between 0.256 inches and 0.270 inches Head Height: Between 0.087 inches and 0.097 inches First Diameter From Head: Between 0.100 inches and 0.104 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.797 inches Internal Drive Style:
Head Height: Between 0.087 inches and 0.097 inches First Diameter From Head: Between 0.100 inches and 0.104 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.797 inches Internal Drive Style:
Between 0.087 inches and 0.097 inches <b>First Diameter From Head:</b> Between 0.100 inches and 0.104 inches <b>Distance From Largest Bearing Surface Of Head To End Of First Diameter:</b> 0.797 inches <b>Internal Drive Style:</b>
First Diameter From Head: Between 0.100 inches and 0.104 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.797 inches Internal Drive Style:
Between 0.100 inches and 0.104 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.797 inches Internal Drive Style:
Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.797 inches Internal Drive Style:
0.797 inches Internal Drive Style:
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Externally Relieved Body Diameter Quantity:
1
Material:
Stainless steel
Surface Treatment:
Passivate
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0