

View Online at <https://aerobasegroup.com/nsn/5305-01-135-2392>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.345 inches and 0.438 inches

Fastener Length:

Between 0.407 inches and 0.438 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.221 inches and 0.226 inches

Head Height:

Between 0.074 inches and 0.086 inches

Locking Feature:

Patch threads

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

24.0 rockwell c and 35.0 rockwell c

Minimum Yield Strength:

85000 pounds per square inch

Surface Finish:

32.0 microinches threads

Material:

Iron alloy 660

Material Specification:

Ams 5737 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjc

Specification Data:

80205-nas1191 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0