NSN 5305-01-135-3530



Machine Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-135-3530 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.157 inches and 0.250 inches **Fastener Length:** Between 0.219 inches and 0.250 inches **Head Style:** Binding **Head Diameter:** Between 0.275 inches and 0.290 inches **Head Height:** Between 0.071 inches and 0.087 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 55000 pounds per square inch **Screw Material:** Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1022 or steel comp 1025 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1040 or steel comp 1108 or steel comp 1109 or steel comp 1110 **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416 type 1 class 3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

Fiig:

A500d0