## NSN 5305-01-135-3533

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-135-3533 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.158 inches and 0.250 inches **Fastener Length:** Between 0.220 inches and 0.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.262 inches and 0.270 inches **Head Height:** Between 0.159 inches and 0.164 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.164 inches Width Across Flats: Between 0.141 inches and 0.143 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 class 3 federal specification single treatment response **Thread Series Designator:** Unrc **Specification Data:** 80205-nas1352 professional/industrial association standard Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-01-135-3533

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0