## NSN 5305-01-135-3534

**Thread Class:** 

**Right-hand** 

**Thread Direction:** 

3a

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-135-3534



### **Thread Length:** Between 0.481 inches and 0.582 inches Fastener Length: Between 0.552 inches and 0.582 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.188 inches and 0.190 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b **Minimum Yield Strength:** 30000 pounds per square inch **Product Name:** Navy special project Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard single material response Surface Treatment: Passivate **Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

#### **Thread Series Designator:**

Unf

#### Shelf Life:

N/a

# NSN 5305-01-135-3534

Socket Head Cap Screw - Page 2 of 2

AeroBase Group

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0