

View Online at <https://aerobasegroup.com/nsn/5305-01-135-3540>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.386 inches and 0.453 inches

Fastener Length:

Between 1.646 inches and 1.693 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.447 inches and 0.507 inches

Grip Diameter:

Between 0.2483 inches and 0.2492 inches

Internal Drive Style:

High-torque

Thread Diameter:

0.250 inches

Grip Length:

Between 1.240 inches and 1.260 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Surface Finish:

32.0 microinches grip

Product Name:

Navy special project

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Cadmium or cadmium and chromate

Surface Treatment Specification:

Nas 672 assn standard 1st treatment response or mil-c-8837 type 2 cl 2 military specification 2nd treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.