

View Online at <https://aerobasegroup.com/nsn/5305-01-135-5294>

**Thread Direction:**

Right-hand

**Thread Length:**

0.187 inches

**Fastener Length:**

0.670 inches

**Head Style:**

Hexagon

**Head Height:**

0.100 inches

**Width Between Flats:**

0.312 inches

**First Diameter From Head:**

0.120 inches

**Second Diameter From Head:**

0.187 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.483 inches

**Single Shear Strength:**

29150 pounds per square inch

**Internal Drive Style:**

Slot

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

40.0 rockwell c

**Minimum Yield Strength:**

160000 pounds per square inch

**Externally Relieved Body Diameter Quantity:**

2

**Material:**

Stainless steel

**Material Specification:**

Qq-s-764 federal specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-f-14072 federal standard single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-f-14072 spec.