NSN 5305-01-135-5294

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-135-5294 **Thread Direction:** Right-hand Thread Length: 0.187 inches Fastener Length: 0.670 inches **Head Style:** Hexagon **Head Height:** 0.100 inches Width Between Flats: 0.312 inches First Diameter From Head: 0.120 inches **Second Diameter From Head:** 0.187 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.483 inches Single Shear Strength: 29150 pounds per square inch **Internal Drive Style:** Slot Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 40.0 rockwell c Minimum Yield Strength: 160000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Stainless steel **Material Specification:** Qq-s-764 federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072 federal standard single treatment response

Unc

Thread Series Designator:

NSN 5305-01-135-5294

Externally Relieved Body Screw - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:
NI-
No
Fiig:

Mil-std (military Standard):

Mil-f-14072 spec.

Shelf Life: