NSN 5305-01-135-6483

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-135-6483 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.660 inches and 0.700 inches **Fastener Length:** Between 0.720 inches and 0.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches **Locking Feature:** Strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.1562 inches and 0.1587 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 42.0 rockwell c Material: Steel comp 8740 **Material Specification:** Mil-s-6049 military specification single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification single treatment response **Thread Series Designator:** Unrf Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-01-135-6483

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.