NSN 5305-01-135-7829



Panel Screw Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-135-7829 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** 0.884 inches **Head Style:** Hexagon **Head Height:** Between 0.181 inches and 0.187 inches

Width Between Flats: Between 0.305 inches and 0.313 inches

Internal Drive Style:

Hexagon

Material Accommodated Thickness:

Between 0.188 inches and 0.250 inches

Thread Diameter:

0.190 inches

Width Across Flats:

0.156 inches

Thready Qty Per Inch (tpi):

Min. Tensile Strength (psi):

80000 pounds per square inch

Material:

Steel comp 302 spring

Material Specification:

Qq-a-255/8 federal specification single material response stand-off

Surface Treatment:

Passivate spring

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spring

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5305-01-135-7829

Panel Screw Assembly - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5059 spec.